ANIMALS CONCEPT
Zoo Equipments

Incubateur / Éclosoir - Ratites

Ces incubateurs offrent des performances semi-professionnelles, grâce à une technologie avancée et un savoir-faire éprouvé.

- **Structure de qualité** : fabriquées avec des panneaux thermiques en tôle galvanisée prépeinte, associée à un isolant en polystyrène. Cela garantit une isolation parfaite et une robustesse à toute épreuve pour une utilisation prolongée.
- **Retourneur d'œufs automatisé** : Un système électromécanique de haute qualité retourne les œufs quotidiennement, favorisant ainsi le développement de l'embryon et évitant les adhérences nuisibles sur la coquille.
- **Surveillance précise** : Le thermomètre en °F et l'hygromètre à bulbe humide assurent une lecture précise de la température et de l'humidité, essentiels pour le bon développement des œufs.
- **Hublot avec éclairage intégré** : Un hublot sur la porte permet de visualiser l'intérieur de l'incubateur, avec un éclairage interne pour une observation facile sans ouvrir la porte.
- **Réglage et contrôle intuitif** : L'affichage LCD permet de régler la température et de lire les valeurs d'humidité avec une grande simplicité, facilitant le contrôle des conditions internes.
- **Ventilation et aération**: L'incubateur est équipé d'un ventilateur professionnel à roulements auto-refroidissants, avec un dispositif permettant d'ajuster l'intensité de la ventilation. Des ouvertures d'aération spécifiques assurent un renouvellement optimal de l'air.
- **Alarme de sécurité** : Une alarme sonore et visuelle signale toute anomalie de température et bloque automatiquement le chauffage si la température maximale définie par l'utilisateur est atteinte.
- **Système d'humidification automatique** : Le bac à couvercles avec un flux d'eau constant maintient un niveau d'humidité stable
- **Tiroirs spécifiques** : Des tiroirs spéciaux sont prévus pour l'incubation de certaines espèces particulières, telles que l'autruche, l'ému et le nandou.

Informations Techniques

- Cabine en acier GALVA

- Capacité MG6SH: Autruches 6
  Emeu 6
  Nandous 6-10
- Capacité MG24SH: Autruches 12
  Emeu 18
  Nandou 12-20

- Options: Humidification externe par ultrasons

Références	Désignation	Dimensions	Poids	Consommation
AC-MG6SH (STEEL)	MG6SH AUTRUCHE	68 x 57 x78 H	27 kg	220 W
AC-MG24SH (STEEL)	MG24SH AUTRUCHE	87 X 88 X 110 H	75 kg	490W

FIEM
INCUBATRICI E SCHIUSE DAL 1975

These incubators offer semi-professional performance, thanks to advanced technology and proven expertise.

- **Quality Structure**: Made with pre-coated galvanized steel thermal panels, combined with a polystyrene insulator. This ensures perfect insulation and durability for long-term use.
- **Automated Egg Turner**: A high-quality electromechanical system turns the eggs daily, promoting embryo development and preventing harmful adhesion to the shell.
- **Precise Monitoring**: The thermometer in °F and wet-bulb hygrometer provide accurate readings of temperature and humidity, essential for the proper development of the eggs.
- **Porthole with Integrated Lighting**: A porthole on the door allows you to view the inside of the incubator, with internal lighting for easy observation without opening the door.
- **Intuitive Adjustment and Control**: The LCD display allows easy temperature adjustment and humidity readings, simplifying the control of internal conditions.
- **Ventilation and Air Circulation**: The incubator is equipped with a professional self-cooling bearing fan, with a system to adjust the ventilation intensity. Specific ventilation openings ensure optimal air renewal.
- **Safety Alarm**: An audible and visual alarm signals any temperature anomaly and automatically disables the heating if the maximum user-defined temperature is reached.
- **Automatic Humidification System**: The constant water flow tray maintains a stable humidity level.
- **Special Drawers**: Specific drawers are designed for the incubation of particular species, such as ostriches, emus, and nandus.

Technical Informations

- GALVA Steel Chamber

- MG6SH Capacity: Ostriches 6
  Emus 6
  Nandus: 6-10
- MG24SH Capacity: Ostriches 12
  Emus 18
  Nandus 12-20

- Options: External Ultrasonic Humidification

Références	Désignation	Dimensions	Poids	Consommation
AC-MG6SH (STEEL)	MG6SH AUTRUCHE	68 x 57 x78 H	27 kg	220 W
AC-MG24SH (STEEL)	MG24SH AUTRUCHE	87 X 88 X 110 H	75 kg	490W

FIEM INCUBATRICI E SCHIUSE DAL 1975